NSN 5305-01-390-3415

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-390-3415

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.750 inches
Fastener Length:
Between 2.670 inches and 2.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.921 inches and 0.937 inches
Head Height:
Between 0.616 inches and 0.625 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
Between 0.500 inches and 0.505 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b fastener
Material:
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or
steel comp xm-7 fastener
Material Specification:
Astm a493 assn standard all material responses fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Astm a380 assn standard single treatment response fastener
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard

N/a

Shelf Life:

NSN 5305-01-390-3415

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0