

View Online at <https://aerobasegroup.com/nsn/5305-01-390-3417>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.312 inches

**Fastener Length:**

Between 0.282 inches and 0.312 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.134 inches and 0.140 inches

**Head Height:**

Between 0.083 inches and 0.086 inches

**Width Between Flats:**

Between 0.0781 inches and 0.0791 inches

**Locking Feature:**

Patch or pellet or strip

**Internal Drive Style:**

Err-090

**Thread Diameter:**

0.086 inches

**Width Across Flats:**

Between 0.0781 inches and 0.0791 inches

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Screw Material:**

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

**Locking Feature Material:**

Plastic polyamide

**Screw Material Specification:**

Astm a493 assn standard all material responses

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Astm a380 assn standard single treatment response

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0