NSN 5305-01-391-0334

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-391-0334 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.656 inches **Fastener Length:** Between 0.688 inches and 0.735 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.838 inches and 0.861 inches **Head Height:** Between 0.286 inches and 0.304 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 or steel comp 4130 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A500d0

NSN 5305-01-391-0334

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.