## NSN 5305-01-391-1413



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-391-1413 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.363 inches **Fastener Length:** Between 1.286 inches and 1.316 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.258 inches and 0.305 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard 1st material response or ams 5732 assn standard 2nd material response or ams 5737 assn standard 3rd material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

**Specification Data:** 

80205-nas1581 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

## NSN 5305-01-391-1413

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0