## NSN 5305-01-391-1442

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-391-1442 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.110 inches and 0.125 inches **Fastener Length:** Between 0.610 inches and 0.640 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.307 inches and 0.327 inches **Head Height:** Between 0.296 inches and 0.328 inches Point Length: 0.078 inches **Point Diameter:** Between 0.062 inches and 0.078 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.474 inches and 0.494 inches Point Style: Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 90.0 degrees Material: Stainless steel **Material Specification:** Astm a581 assn standard single material response or astm a582 assn standard single material response **Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Mil-f-14072-e300 military specification single treatment response

## NSN 5305-01-391-1442

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-f-14072-e300 spec.