NSN 5305-01-391-3584

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-391-3584

•
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.375 inches
Fastener Length:
Between 3.860 inches and 3.890 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.625 inches and 0.635 inches
Grip Diameter:
Between 0.3106 inches and 0.3112 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.313 inches
Grip Length:
Between 3.490 inches and 3.510 inches
Thready Qty Per Inch (tpi):
24
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
3.7576 inches first hole
Special Features:
Offset curciform recess per ms33781 or ms14191
Material:
Titanium alloy uns r56400
Material Specification:
Ams4967 assn standard single material response
Thread Series Designator:
Unif
Specification Data:
80205-nas 1155 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-391-3584

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0