Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-391-3585

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.000 inches
Fastener Length:
1.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.244 inches and 0.250 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.1875 inches and 0.1900 inches
Hole Quantity:
6
Ноје Туре:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 45.0 rockwell c
Hole Configuration Style:
Round internal hexagon
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard 1st material response or ams 5737 assn standard 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification all treatment responses

NSN 5305-01-391-3585

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A003b0