NSN 5305-01-391-4382

Machine Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-391-4382

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.750 inches |
| Fastener Length: |
| Between 0.719 inches and 0.750 inches |
| Head Style: |
| Flat fillister |
| Head Diameter: |
| Between 0.221 inches and 0.226 inches |
| Head Height: |
| Between 0.074 inches and 0.086 inches |
| Locking Feature: |
| Strip |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.1380 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Screw Material: |
| Iron alloy 660 |
| Locking Feature Material: |
| Plastic polyamide |
| Screw Material Specification: |
| Ams 5737, a286 assn standard single material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1191 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-01-391-4382 Machine Screw - Page 2 of 2

Fiig: A500d0

