## NSN 5305-01-391-9689

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-391-9689 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 2.500 inches **Fastener Length:** 2.500 inches **Head Height:** 0.233 inches Width Between Flats: 0.640 inches **Shank Unthreaded Hole Diameter:** 0.121 inches first hole and 0.125 inches first hole **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.344 inches first hole Material: Steel comp 410 or steel comp 416 or steel comp 430 **Material Specification:** Fed standard 66 federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-01-391-9689

Hexagon Head Cap Screw - Page 2 of 2



Fiig:

A003b0