NSN 5305-01-392-0130

Machine Screw - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5305-01-392-0130

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.429 inches and 0.531 inches
Fastener Length:
Between 0.484 inches and 0.531 inches
Head Style:
Hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp e4340 and steel comp 8740
Screw Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1801 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

NSN 5305-01-392-0130

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.