NSN 5305-01-392-0587

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-392-0587 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** 1.750 inches **Head Style:** Hexagon **Head Height:** Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches **First Diameter From Head:** Between 0.260 inches and 0.280 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches **Internal Drive Style:** W/o internal drive **End Application:** C17a serd 100502 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Altered item, make from ms35307-365 Material: Steel comp 302 or steel comp 303 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Unc

Thread Series Designator:

NSN 5305-01-392-0587

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0