## NSN 5305-01-392-1639

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-392-1639 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.250 inches **Fastener Length:** 1.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.313 inches and 0.316 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Special Features:** Undercut under head-length 0.030 inb min. And 0.033 in. Max; radius 0.010 in. Max. Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Fed standard 66 federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrf

Shelf Life: N/a

## NSN 5305-01-392-1639

Socket Head Cap Screw - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0