## NSN 5305-01-392-2595

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-392-2595

3a Thread Direction: Right-hand Thread Length: 0.498 inches Fastener Length: Between 0.921 inches and 0.951 inches Head Style: Flat countersunk Head Diameter: Between 0.447 inches and 0.507 inches
Right-hand Thread Length: 0.498 inches Fastener Length: Between 0.921 inches and 0.951 inches Head Style: Flat countersunk Head Diameter:
Thread Length: 0.498 inches Fastener Length: Between 0.921 inches and 0.951 inches Head Style: Flat countersunk Head Diameter:
0.498 inches Fastener Length: Between 0.921 inches and 0.951 inches Head Style: Flat countersunk Head Diameter:
Fastener Length:         Between 0.921 inches and 0.951 inches         Head Style:         Flat countersunk         Head Diameter:
Between 0.921 inches and 0.951 inches Head Style: Flat countersunk Head Diameter:
Head Style: Flat countersunk Head Diameter:
Flat countersunk Head Diameter:
Head Diameter:
Between 0 447 inches and 0 507 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Single Shear Strength:
132000 pounds per square inch
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
0.438 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
240000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Cobalt comp mp-35-n
Material Specification:
Amss 5844 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-392-2595

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

