NSN 5305-01-392-2600

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-392-2600

3aThread Direction:Right-handThread Length:0.498 inchesFastener Length:Between 1.296 inches and 1.326 inchesHead Style:Flat countersunkHead Diameter:Between 0.447 inches and 0.507 inchesGrip Diameter:Between 0.2485 inches and 0.2495 inchesSingle Shear Strength:132000 pounds per square inchInternal Drive Style:Offset cruciform (torque set)
Right-hand Thread Length: 0.498 inches Fastener Length: Between 1.296 inches and 1.326 inches Head Style: Flat countersunk Head Diameter: Between 0.447 inches and 0.507 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
Thread Length: 0.498 inches Fastener Length: Between 1.296 inches and 1.326 inches Head Style: Flat countersunk Head Diameter: Between 0.447 inches and 0.507 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
0.498 inches Fastener Length: Between 1.296 inches and 1.326 inches Head Style: Flat countersunk Head Diameter: Between 0.447 inches and 0.507 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
Fastener Length:Between 1.296 inches and 1.326 inchesHead Style:Flat countersunkHead Diameter:Between 0.447 inches and 0.507 inchesGrip Diameter:Between 0.2485 inches and 0.2495 inchesSingle Shear Strength:132000 pounds per square inchInternal Drive Style:
Between 1.296 inches and 1.326 inches Head Style: Flat countersunk Head Diameter: Between 0.447 inches and 0.507 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
Head Style: Flat countersunk Head Diameter: Between 0.447 inches and 0.507 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
Flat countersunk Head Diameter: Between 0.447 inches and 0.507 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
Head Diameter: Between 0.447 inches and 0.507 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
Between 0.447 inches and 0.507 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
Grip Diameter: Between 0.2485 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
Between 0.2485 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
Single Shear Strength: 132000 pounds per square inch Internal Drive Style:
132000 pounds per square inch Internal Drive Style:
132000 pounds per square inch Internal Drive Style:
Internal Drive Style:
-
Thread Diameter:
0.250 inches
Grip Length:
0.813 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
240000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Cobalt comp mp-35-n
Material Specification:
Ams 5844 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-392-2600

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

