

View Online at <https://aerobasegroup.com/nsn/5305-01-392-3461>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 2.028 inches and 2.250 inches

**Fastener Length:**

2.250 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 1.293 inches and 1.312 inches

**Head Height:**

Between 0.864 inches and 0.875 inches

**Locking Feature:**

Patch threads or strip threads or pellet threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.875 inches

**Width Across Flats:**

Between 0.750 inches and 0.757 inches

**Thready Qty Per Inch (tpi):**

9

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c fastener and 45.0 rockwell c fastener

**Minimum Yield Strength:**

155000 pounds per square inch

**Surface Finish:**

63.0 microinches fastener

**Color:**

Black fastener

**Material:**

Steel fastener

**Material Specification:**

Fed 66 federal standard all material responses fastener

**Surface Treatment:**

Oxide fastener

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response fastener

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.