

View Online at <https://aerobasegroup.com/nsn/5305-01-392-3461>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 2.028 inches and 2.250 inches

Fastener Length:

2.250 inches

Head Style:

Flat chamfer

Head Diameter:

Between 1.293 inches and 1.312 inches

Head Height:

Between 0.864 inches and 0.875 inches

Locking Feature:

Patch threads or strip threads or pellet threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.875 inches

Width Across Flats:

Between 0.750 inches and 0.757 inches

Thread Qty Per Inch (tpi):

9

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c fastener and 45.0 rockwell c fastener

Minimum Yield Strength:

155000 pounds per square inch

Surface Finish:

63.0 microinches fastener

Color:

Black fastener

Material:

Steel fastener

Material Specification:

Fed 66 federal standard all material responses fastener

Surface Treatment:

Oxide fastener

Surface Treatment Specification:

Mil-c-13924 military specification single treatment response fastener

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.