

View Online at <https://aerobasegroup.com/nsn/5305-01-392-6432>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.344 inches and 0.375 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.172 inches

**Locking Feature:**

Patch

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.086 inches

**Features Provided:**

O ring

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

75000 pounds per square inch

**Countersink Angle:**

Between 81.0 degrees and 83.0 degrees

**Screw Material:**

Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

**Locking Feature Material:**

Plastic polyamide

**Screw Material Specification:**

Qq-s-763 federal specification all material responses or astm a493 assn standard all material responses

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Special Features:**

O ring matl.: composition a per mil-s-82496

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0