NSN 5305-01-392-6438

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-392-6438

Thread Class: 2a Thread Direction: Right-hand Thread Length: 0.187 inches Fastener Length: Between 0.156 inches and 0.187 inches Head Style: Pan no. 2 Head Diameter: 0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material: Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Thread Direction: Right-hand Thread Length: 0.187 inches Fastener Length: Between 0.156 inches and 0.187 inches Head Style: Pan no. 2 Head Diameter: 0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Right-hand Thread Length: 0.187 inches Fastener Length: Between 0.156 inches and 0.187 inches Head Style: Pan no. 2 Head Diameter: 0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Thread Length: 0.187 inches Fastener Length: Between 0.156 inches and 0.187 inches Head Style: Pan no. 2 Head Diameter: 0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
O.187 inches Fastener Length: Between 0.156 inches and 0.187 inches Head Style: Pan no. 2 Head Diameter: 0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Fastener Length: Between 0.156 inches and 0.187 inches Head Style: Pan no. 2 Head Diameter: 0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Between 0.156 inches and 0.187 inches Head Style: Pan no. 2 Head Diameter: 0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Head Style: Pan no. 2 Head Diameter: 0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Pan no. 2 Head Diameter: 0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Head Diameter: 0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
0.176 inches Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Head Height: 0.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
O.057 inches Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: O.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Locking Feature: Patch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Cross recess type 1 Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Thread Diameter: 0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
0.086 inches Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Features Provided: O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
O ring Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
Min. Tensile Strength (psi): 75000 pounds per square inch Screw Material:
75000 pounds per square inch Screw Material:
Screw Material:
Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Clock complete it allock complete of allock complete of allock complete it allock complete it.
Locking Feature Material:
Plastic polyamide
Screw Material Specification:
Qq-s-763 federal specification all material responses or astm a493 assn standard all material responses
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Special Features:
O ring matl.: composition a per mil-s-82496
Thread Series Designator:
Unc
Shelf Life:
N/a

NSN 5305-01-392-6438

Machine Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A500d0