NSN 5305-01-393-2966

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-393-2966

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.250 inches
Fastener Length:
Between 0.219 inches and 0.250 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.205 inches and 0.219 inches
Head Height:
0.075 inches
Locking Feature:
Pellet
Internal Drive Style:
Torque set
End Application:
Pacer dawn
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polyamide
Screw Material Specification:
Ams5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1190 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-393-2966

Machine Screw - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0