## NSN 5305-01-393-6121

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-393-6121 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.213 inches and 0.233 inches **Fastener Length:** 0.930 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** 0.110 inches **First Diameter From Head:** 0.164 inches **Second Diameter From Head:** Between 0.104 inches and 0.233 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.023 inches and 0.026 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Pacer dawn **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams5737 federal specification single material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unc

## NSN 5305-01-393-6121

Externally Relieved Body Screw - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0