NSN 5305-01-393-9950

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-393-9950 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 3.500 inches **Head Style:** Pan **Head Diameter:** 0.312 inches **Head Height:** 0.120 inches **First Diameter From Head:** 0.188 inches **Second Diameter From Head:** 0.312 inches **Third Diameter From Head:** 0.188 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.880 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Steel comp 303 or steel comp 303ma or steel comp 303pb or steel comp 303 plus x or steel comp 303se **Material Specification:** Astm a582 ty303 assn standard single material response **Surface Treatment: Passivate**

Surface Treatment Specification:

Qq-p-35, tyii federal specification single treatment response

NSN 5305-01-393-9950

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0