## NSN 5305-01-394-0355

Machine Screw - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

За

N/a



View Online at https://aerobasegroup.com/nsn/5305-01-394-0355

Right-hand
Thread Length:
0.344 inches
Fastener Length:
Between 0.344 inches and 0.375 inches
Head Style:
Flat countersunk
Head Diameter:
0.219 inches
Locking Feature:
Strip
Internal Drive Style:
Torque set
End Application:
Pacer dawn
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
160000 pounds per square inch  Countersink Angle:
Countersink Angle:
Countersink Angle: 100.0 degrees
Countersink Angle: 100.0 degrees Screw Material:
Countersink Angle: 100.0 degrees Screw Material: Iron alloy 660
Countersink Angle: 100.0 degrees Screw Material: Iron alloy 660 Locking Feature Material:
Countersink Angle: 100.0 degrees Screw Material: Iron alloy 660 Locking Feature Material: Plastic polyamide
Countersink Angle: 100.0 degrees Screw Material: Iron alloy 660 Locking Feature Material: Plastic polyamide Screw Material Specification:
Countersink Angle:  100.0 degrees  Screw Material:  Iron alloy 660  Locking Feature Material:  Plastic polyamide  Screw Material Specification:  Ams5737 assn standard single material response
Countersink Angle:  100.0 degrees  Screw Material: Iron alloy 660  Locking Feature Material:  Plastic polyamide  Screw Material Specification:  Ams5737 assn standard single material response  Screw Surface Treatment:
Countersink Angle:  100.0 degrees  Screw Material:  Iron alloy 660  Locking Feature Material:  Plastic polyamide  Screw Material Specification:  Ams5737 assn standard single material response  Screw Surface Treatment:  Passivate
Countersink Angle:  100.0 degrees  Screw Material:  Iron alloy 660  Locking Feature Material:  Plastic polyamide  Screw Material Specification:  Ams5737 assn standard single material response  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:
Countersink Angle:  100.0 degrees  Screw Material: Iron alloy 660  Locking Feature Material:  Plastic polyamide  Screw Material Specification:  Ams5737 assn standard single material response  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Countersink Angle:  100.0 degrees  Screw Material:  Iron alloy 660  Locking Feature Material:  Plastic polyamide  Screw Material Specification:  Ams5737 assn standard single material response  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:
Countersink Angle:  100.0 degrees  Screw Material: Iron alloy 660  Locking Feature Material: Plastic polyamide  Screw Material Specification: Ams5737 assn standard single material response  Screw Surface Treatment: Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator: Unjc

## NSN 5305-01-394-0355

Machine Screw - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A500d0