## NSN 5305-01-394-3925

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-394-3925

Thread Class
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.323 inches
Fastener Length:
Between 0.684 inches and 0.713 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.266 inches and 0.303 inches
Head Height:
0.049 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Single Shear Strength:
95000 pounds per square inch
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Grip Length:
Between 0.365 inches and 0.385 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard 1st material response or ams 5737 assn standard 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2, cl2 federal specification all treatment responses
Thread Series Designator:

Unjf

## NSN 5305-01-394-3925

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0