NSN 5305-01-394-4503

Thread Class:

Thread Direction:

2a

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-394-4503

Right-hand
Thread Length:
Between 1.167 inches and 1.250 inches
Fastener Length:
1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.430 inches and 0.437 inches
Hole Diameter:
Between 0.061 inches and 0.067 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b fastener
Minimum Yield Strength:
30000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel fastener
Material Specification:

Astm a493 assn standard all material responses fastener

NSN 5305-01-394-4503

Socket Head Cap Screw - Page 2 of 2



Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0