## NSN 5305-01-394-5975

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-394-5975 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.693 inches **Fastener Length:** 4.125 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.977 inches and 1.000 inches **Head Height:** Between 0.492 inches and 0.500 inches **Shoulder Diameter:** 0.747 inches first shoulder and 0.748 inches first shoulder **Shoulder Length:** 3.157 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: 0.375 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder **Special Features:** Side of head may be plain or knurled. Threads and shoulder are undercut for relief. Material: Steel **Surface Treatment:** Oxide threads **Thread Series Designator:** Unrc

Shelf Life:

N/a

## NSN 5305-01-394-5975

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0