NSN 5305-01-394-5977

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-394-5977 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.460 inches **Fastener Length:** Between 1.070 inches and 1.200 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.390 inches and 0.395 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches grip and 0.081 inches grip **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.615 inches and 0.635 inches **Features Provided:** Dry film lubricant Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.899 inches first hole and 0.949 inches first hole **Special Features:** Domed head Material: Titanium alloy uns r56400 **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-394-5977

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0