

View Online at <https://aerobasegroup.com/nsn/5305-01-394-5977>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.460 inches

**Fastener Length:**

Between 1.070 inches and 1.200 inches

**Head Style:**

Oval countersunk

**Head Diameter:**

Between 0.390 inches and 0.395 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches grip and 0.081 inches grip

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.615 inches and 0.635 inches

**Features Provided:**

Dry film lubricant

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.899 inches first hole and 0.949 inches first hole

**Special Features:**

Domed head

**Material:**

Titanium alloy uns r56400

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0