

View Online at <https://aerobasegroup.com/nsn/5305-01-395-1402>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.508 inches

**Fastener Length:**

Between 0.527 inches and 0.558 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.213 inches and 0.225 inches

**Internal Drive Style:**

Cross recess type iii

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp 4130 or steel comp 4340 or steel comp 8740

**Screw Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses

**Color:**

Black

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas514 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6758 spec.