## NSN 5305-01-395-1402

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-395-1402 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.508 inches **Fastener Length:** Between 0.527 inches and 0.558 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.213 inches and 0.225 inches **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4130 or steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-6758 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses Color: Black **Thread Series Designator:** Unjc **Specification Data:** 80205-nas514 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:** 

## NSN 5305-01-395-1402

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.