NSN 5305-01-395-1402

Machine Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-395-1402

| Thread Class: | |
|-----------------------|---|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.508 inches | |
| Fastener Length: | |
| Between 0.527 inche | s and 0.558 inches |
| Head Style: | |
| Flat countersunk | |
| Head Diameter: | |
| Between 0.213 inche | s and 0.225 inches |
| Internal Drive Style | |
| Cross recess type iii | |
| Thread Diameter: | |
| 0.112 inches | |
| Thready Qty Per Inc | h (tpi): |
| 40 | |
| Countersink Angle: | |
| Between 99.0 degree | s and 101.0 degrees |
| Screw Material: | |
| Steel comp 4130 or | teel comp 4340 or steel comp 8740 |
| Screw Material Spe | ification: |
| Mil-s-6758 military s | ecification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military |
| specification 3rd mat | arial response |
| Screw Surface Trea | ment: |
| Cadmium and chrom | ate |
| Screw Surface Trea | ment Specification: |
| Qq-p-416, type 2, c | ass 2 federal specification all treatment responses |
| Color: | |
| Black | |
| Thread Series Desi | nator: |
| Unjc | |
| Specification Data: | |
| 80205-nas514 profe | sional/industrial association standard |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A500d0 | |

NSN 5305-01-395-1402

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-6758 spec.

