## NSN 5305-01-395-3583

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-395-3583 **Thread Class: Thread Direction:** Right-hand Fastener Length: 0.960 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.490 inches and 0.523 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** 0.250 inches **Thread Diameter:** 0.250 inches Width Across Flats: 0.220 inches **Features Provided:** Dry film lubricant Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Lead Thread Quantity:** Two **Special Features:** Internal threads Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Passivate and lubricant **Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response and mil-l-46010, type 1, kal-gard ty fa military specification 2nd treatment response **Thread Series Designator:** Unjf

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5305-01-395-3583

Panel Screw Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-I-46010 spec.