## NSN 5305-01-395-9650

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-395-9650

Thread Class:

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.318 inches and 1.500 inches
Fastener Length:
1.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.921 inches and 0.938 inches
Head Height:
Between 0.616 inches and 0.625 inches
Locking Feature:
Pellet threads or strip threads or patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
0.500 inches
Thready Qty Per Inch (tpi):
11
Min. Tensile Strength (psi):
105000 pounds per square inch
Minimum Yield Strength:
50000 pounds per square inch
Material:
Steel comp 304 fastener or steel comp 305 fastener
Material Specification:
Astm a493 assn standard 1st material response fastener or astm a493 assn standard 2nd material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-395-9650

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0