
Socket Head Cap Screw - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.318 inches and 1.500 inches

Fastener Length:

1.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.921 inches and 0.938 inches

Head Height:

Between 0.616 inches and 0.625 inches

Locking Feature:

Pellet threads or strip threads or patch threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.625 inches

Width Across Flats:

0.500 inches

Thready Qty Per Inch (tpi):

11

Min. Tensile Strength (psi):

105000 pounds per square inch

Minimum Yield Strength:

50000 pounds per square inch

Material:

Steel comp 304 fastener or steel comp 305 fastener

Material Specification:

Astm a493 assn standard 1st material response fastener or astm a493 assn standard 2nd material response fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5305-01-395-9650

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

