Socket Head Cap Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-396-1038

3a Thread Direction: Right-hand Thread Longth: Between 0.792 inches and 0.875 inches Fastener Length: 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Diameter: Between 0.368 inches and 0.375 inches Locking Feature: Stip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.375 inches Width Across Flats: 0.375 inches Width Across Flats: 0.312 inches Thready Cty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 105000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Attre Specification: Thread Series Designator: Uri Specifi	Thread Cl	ass:
Right-hand Thread Length: Between 0.792 inches and 0.875 inches Fastener Length: 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Lecking Feature: Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches With Across Flats: 0.375 inche	3a	
Tread Length: Between 0.792 inches and 0.875 inches Fastener Length: 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Locking Feature: Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.312 inches Thready Oty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 85000 pounds per square inch 85000 pounds per square inch 85000 pounds per squ	Thread Di	rection:
Between 0.792 inches and 0.875 inches Fastener Length: 0.875 inches Head Siyle: Flat chamfer Head Diameter: Between 0.560 inches and 0.562 inches Head Height: Between 0.368 inches and 0.562 inches Locking Feature: Strip threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.375 inches Strip thread (ps)): 105000 pounds per square inch Minimum Yield Strength Edit (ps) Steel comp 304 fastener or steel comp 305 fastener Material Specification: Atternal Specification Steel comp 305 fastener Steel Comp 3	Right-hand	I
Fastener Length: 0.875 inches Head Style: Flat chamfer Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.586 inches and 0.375 inches Locking Feature: Strip threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.375 inches Width Across Flats: 0.375 inches Width Across Flats: 0.372 inches Thread Val Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: Na Unit Of Measure: Thread Se	Thread Le	ngth:
0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Locking Feature: Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.312 inches Width Across Flats: 0.320 pounds per square inch Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material: Steel comp 304 fastener or steel comp 305 fastener Thread Series Designator: Urf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: -	Between 0	.792 inches and 0.875 inches
Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Locking Feature: Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.375 inches Width Across Flats: 0.371 inches Width Across Flats: 0.372 inches Wintensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: Via	Fastener I	_ength:
Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Locking Feature: Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.375 inches Width Across Flats: 0.372 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Miterial: Steel comp 304 fastener or steel comp 305 fastener Material Steel form 304 fastener or steel comp 305 fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Uni Of Measure:	0.875 inch	es
Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Locking Feature: Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.375 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material: Steel comp 304 fastener or steel comp 305 fastener Thread Series Designator: Unf Specification Or Standard: 2 type Sheft Life: N/a Unit Of Measure: To	Head Style	9:
Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Locking Feature: Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.375 inches Width Across Flats: 0.372 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fatstener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Sheff Life: N/a Uni Of Measure:	Flat chamf	er
Head Height: Between 0.368 inches and 0.375 inches Locking Feature: Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.371 inches Width Across Flats: 0.372 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: To	Head Dian	neter:
Between 0.368 inches and 0.375 inches Locking Feature: Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.375 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure:	Between 0	.550 inches and 0.562 inches
Locking Feature: Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm 1593 assn standard 1st material response fastener or asm 1593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Uni Of Measure:	Head Heig	ht:
Strip threads or pellet threads or patch threads Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm 1593 assn standard 1st material response fastener or asm 1593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure:	Between 0	.368 inches and 0.375 inches
Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: -	Locking F	eature:
Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure:	Strip threa	ds or pellet threads or patch threads
Thread Diameter: 0.375 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm 1593 assn standard 1st material response fastener or asm 1593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: -	Internal D	rive Style:
0.375 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Hexagon	
Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Thread Dia	ameter:
0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure:	0.375 inch	es
Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Width Acr	oss Flats:
24 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	0.312 inch	es
Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Thready C	tty Per Inch (tpi):
105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	24	
Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Min. Tens	ile Strength (psi):
65000 pounds per square inch Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	105000 po	unds per square inch
Material: Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Minimum	Yield Strength:
Steel comp 304 fastener or steel comp 305 fastener Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure:	65000 pou	nds per square inch
Material Specification: Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Material:	
Astm f593 assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastener Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Steel comp	o 304 fastener or steel comp 305 fastener
Thread Series Designator: Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Material S	pecification:
Unf Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Astm f593	assn standard 1st material response fastener or asm f593 assn standard 2nd material response fastene
Specification Or Standard: 2 type Shelf Life: N/a Unit Of Measure: 	Thread Se	ries Designator:
2 type Shelf Life: N/a Unit Of Measure:	Unf	
Shelf Life: N/a Unit Of Measure: 	Specificat	ion Or Standard:
N/a Unit Of Measure:	2 type	
Unit Of Measure:	Shelf Life:	
	N/a	
	Unit Of Me	easure:
Demilitarization:		
	Demilitari	zation:

NSN 5305-01-396-1038

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

