NSN 5305-01-396-4352

Externally Relieved Body Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-396-4352



Thread Class: За **Thread Direction:** Right-hand Thread Length: 0.170 inches **Fastener Length:** 0.525 inches **Head Style:** Hexagon **Head Height:** Between 0.079 inches and 0.082 inches Width Between Flats: Between 0.244 inches and 0.250 inches **First Diameter From Head:** Between 0.120 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.355 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 36 Hardness Rating: 38.0 rockwell c **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material: Steel comp 8740 **Material Specification:** Mil-s-6049 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unrf Shelf Life: N/a

NSN 5305-01-396-4352

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure	U	nit	Of	Meas	ure	:
-----------------	---	-----	----	------	-----	---

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.