## NSN 5305-01-396-9651

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-396-9651 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.578 inches and 0.593 inches **Fastener Length:** Between 1.078 inches and 1.093 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.385 inches and 0.395 inches **Head Height:** Between 0.172 inches and 0.187 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Product Name:** Navy special project Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

\_\_

**Unit Of Measure:** 

## NSN 5305-01-396-9651

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0