Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-397-0890

Thread Class: 2a Thread Infoction: Right-hand Thread Length: 1.030 inches Eastener Length: Between 1.300 inches and 1.440 inches Head Siyle: Fillster Head Diameter: Between 0.070 inches and 0.219 inches Head Height: Between 0.070 inches Head Head Head Head Head Head Head Head	
Thread Direction: Right-hand Thread Length: 1.030 inches Fastener Length: Between 1.300 inches and 1.440 inches Head Style: Filleter Head Diameter: Between 0.205 inches and 0.219 inches Between 0.205 inches and 0.219 inches Between 0.205 inches and 0.219 inches Between 0.205 inches and 0.080 inches Iternal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Ver Inch (tpi): 10 Thread Ver Inch (tpi): 112 12 Material: Stele	Thread Class:
Right-hand Thread Length: 1.300 inches Patter Length: Between 1.300 inches and 1.440 inches Head Style: Fillister Head Diameter: Between 0.205 inches and 0.219 inches Head Height: Between 0.205 inches and 0.219 inches Head Height: Between 0.205 inches and 0.080 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Vier Pinch (tpl): 40 Externally Relieved Body Diameter Quantity: 1 Matrial: Stele Surface Treatment: Passivate Dirit Life: Na Dirit Component: Passivate Dirit Life: Na Dirit Componeti Supplicitation single treatment response<	
Thread Length: 1.030 inches Fastener Length: Between 1.330 inches and 1.440 inches Head Skyle: Filiater Head Diameter: Between 0.020 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Skyle: Cross receases type 1 Thread Diameter: 0.112 inches Thread Ver Per Inch (tpi): 40 Marrial: Stele Stele <	
1.030 inches Fastener Length: Between 1.380 inches and 1.440 inches Head Style: Fillister Head Diameter: Between 0.020 inches and 0.219 inches Head Height: Between 0.070 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread V Per Inch (tpl): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stel Stel StarGer Treatment Specification: Quep-35, tyli federal specification single treatment response Thread Series Designator: Unc Stel Stel Lite: Na Na Na Diried Measure: Interd Series Designator: Na Diried Measure: Interd Series Designator: Na Diried Measure: Na Diried Measure: <th></th>	
Fastener Length: Between 1.380 inches and 1.440 inches Head Style: Fillistor Fillistor Head Style: Fillistor Head Oinmeter: Between 0.205 inches and 0.219 inches Head Height: Between 0.707 inches and 0.080 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Vier Per Inch (tpi): 10 Externally Relieved Body Diameter Quantity: 1 Quer Style Stele Surface Treatment Query-5s, tyil federal specification Query-5s, tyil federal specification single treatment response Thread Series Designator: Quer Yei Mainelistizzzzzzzzzzzzzzzzzzzzzzzzzzzzzzzzzzz	Thread Length:
Between 1.380 inches and 1.440 inches Filister Filister Between 0.205 inches and 0.219 inches Between 0.205 inches and 0.219 inches Head Diameter: Between 0.070 inches and 0.080 inches Internal Drive Style: Cross receas type 1 Thread Diameter: 0.112 inches Pread Quty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stele Surface Treatment: Passivale Quep-35, tyli federal specification single treatment response Thread Series Designator: Unc Stel Strice Treatment Specification: Quep-35, tyli federal specification single treatment response Thread Series Designator: Unc Strice Na Differie: Na Differie: Na Differie: Na Stele Differie: Differie: Differie: Diffe	
Head Style: Filiater Head Diameter: Between 0.205 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Diameter: 0 Sternally Relieved Body Diameter Quantity: 1 Materia: Stele Surface Treatment: Passivate Quep-35, tyli federal specification single treatment response Thread Series Designator: Unc Stel Stel Stel Streat Rest Designator: Unc Stel Stel Stel Stel Stel Stel Direct Treatment Specification Stell Stell Stell Stell Stell Stell	
Filister Head Diameter: Between 0.0205 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Prose recess type 1 Thread Diameter: 0.112 inches Thread Valve Finch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel Surface Treatment: Passivate Query St, bij federal specification single treatment response Thread Series Designator: Unc Stefl Life: Na Dir Gensen:	Between 1.380 inches and 1.440 inches
Head Diameter: Between 0.205 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Valve Per Inch (tpi): 0 Thready Oty Per Inch (tpi): 1 Material: Steel Sterally Relieved Body Diameter Quantity: 1 Material: Steel Sterally Relieved Index Specification Auge-35, tyli federal specification single treatment response Thread Series Designator: Unc Shel In: Na Did Measure: Finiliarization: Na Na Shell Hot Of Measure: Shell In: Na Hot Of Measure: Finiliarization: Na Shell Intertertertertertertertertertertertertert	Head Style:
Between 0.205 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Parl Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel Sterl Starface Treatment: Passivate Durye-35, tyli federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: - Pamiliatrization: No Fig:	Fillister
Head Height:Between 0.070 inches and 0.080 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.112 inchesThready dty Per Inch (tpi):40Externally Relieved Body Diameter Quantity:1Material:SteelSurface Treatment:PassivateQuep-35, tyli federal specification:UncSheff Life:NaDired Steiles Designator:UncSheff Life:NaDired Treatment:NaDired Treatment:Dired Steiles Designator:UncSheff Life:NaDired Treatment:NaDired Steiles Designator:UncSheff Life:NaDired Treatment:NaFig:NaSteiles Designator:Thread Steiles Designator:Dired Steiles Designator:Dired Steiles Designator:The Dired Steiles Designator:Steiles Designator:Thread Steiles Designator:Dired Steiles Designator:Steiles Designator: <th>Head Diameter:</th>	Head Diameter:
Between 0.070 inches and 0.080 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stel Surface Treatment: Passivate Ourp-55, tyli federal specification single treatment response Thread Series Designator: Unc Sheff Life: Na Ditt Of Measure: Image: No Fig:	Between 0.205 inches and 0.219 inches
Iternal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Oty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel Steal Sterator Treatment: Passivate Org-p-35, tyli federal specification single treatment response Thread Series Designator: Unc Sheff Life: N/a Unc Sheff Life: N/a Ditt Of Measure: Image: No Fig:	
Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel Steel Steel Steat Steat Charaet Treatment: Passivate Qu-p-35, tyli federal specification single treatment response Thread Series Designator: Unc Sheff Life: N/a Unc Fig: N/a	Between 0.070 inches and 0.080 inches
Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel Surface Treatment: Passivate Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35, tyli federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unc Shelf Life: N/a Din of Measure: Demilitarization: No Fig:	
0.112 inchesThready Qty Per Inch (tpi):40Externally Relieved Body Diameter Quantity:1Material:SteelSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35, tyli federal specification single treatment responseThread Series Designator:UncShelf Life:N/aDing Masure:Formilitarization:NaFig:NaStellStell <th></th>	
Thready Qty Per Inch (tpi):40Externally Relieved Body Diameter Quantity:11Material:SteelSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35, tyii federal specification single treatment responseThread Series Designator:UncShelf Life:N/aDint of Measure:-Dint of Measure:-Dint of Measure:NaFig:Na	
40 Externally Relieved Body Diameter Quantity: 1 1 Metrial: Steel Surface Treatment: Passivate Surface Treatment Specification: Acq-p-35, tyli federal specification single treatment response Chread Series Designator: Unc Sheff Life: N/a Dirt Of Measure: - Demiltarization: No Sig:	
Externally Relieved Body Diameter Quantity:11Material:SteelSurface Treatment:PassivateQr.p-35, tyli federal specification single treatment responseThread Series Designator:UncShelf Life:N/aDint of Measure:Demiltarization:NoFig:	
1Material:SteelSurface Treatment:PassivateSurface Treatment Specification:Q-p-35, tyli federal specification single treatment responseThread Series Designator:UncShelf Life:N/aInt of Measure:Smilitarization:NoFig:	
Material:SteelSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35, tyii federal specification single treatment responseThread Series Designator:UncShelf Life:N/aDitt Of Measure:Smilitarization:NoFig:	Externally Relieved Body Diameter Quantity:
SteelSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35, tyli federal specification single treatment responseThread Series Designator:UncShelf Life:N/aDirt Of Measure:Demilitarization:NoFig:	
Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35, tyii federal specification single treatment responseThread Series Designator:UncShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	
Passivate Surface Treatment Specification: Qq-p-35, tyli federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	
Surface Treatment Specification: Qq-p-35, tyii federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Qq-p-35, tyii federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	
A003b0	
	A003b0