

View Online at <https://aerobasegroup.com/nsn/5305-01-398-1270>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.363 inches

**Fastener Length:**

Between 1.098 inches and 1.128 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.2578 inches and 0.3047 inches

**Shoulder Diameter:**

0.2041 inches first shoulder and 0.2051 inches first shoulder

**Shoulder Length:**

0.697 inches first shoulder and 0.717 inches first shoulder

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1581 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.