

View Online at <https://aerobasegroup.com/nsn/5305-01-398-1271>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.719 inches and 0.750 inches

Fastener Length:

Between 0.719 inches and 0.750 inches

Head Style:

Pan

Head Diameter:

Between 0.473 inches and 0.492 inches

Head Height:

Between 0.162 inches and 0.175 inches

Locking Feature:

Patch

Internal Drive Style:

Torque set

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Locking Feature Material:

Plastic polyamide

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-8844 military specification 2nd material response or ams 6414 assn standard
2nd material response or mil-s-6049 military specification 3rd material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416 type 1 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1190 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.