NSN 5305-01-398-3584

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-398-3584

Inread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.388 inches and 0.438 inches
Fastener Length:
Between 0.407 inches and 0.438 inches
Head Style:
Flat fillister
Head Diameter:
Between 0.265 inches and 0.270 inches
Head Height:
Between 0.059 inches and 0.069 inches
Locking Feature:
Patch
Internal Drive Style:
Torque set
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polyamide
Screw Material Specification:
Ams5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1191 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-398-3584

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0