NSN 5305-01-398-6311

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-398-6311 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.198 inches **Fastener Length:** Between 0.281 inches and 0.312 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel **Screw Material Specification:** Qq-s-697 federal specification single material response or fed-std66 federal standard single material response **Screw Surface Treatment:** Zinc and chromate **Screw Surface Treatment Specification:** Mil-std-171 1.9.2.3 military standard single treatment response **Special Features:** Surface treatment per mil-std-171 except: 0.0003 in. Thick and supplementary chromate treatment to be olive drab or bronze Color: Olive drab or bronze **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-398-6311

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-std-171 spec.