NSN 5305-01-398-6336

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-398-6336

| Thread Class: | |
|-----------------------|---|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.498 inches | |
| Fastener Length: | |
| Between 1.252 inche | es and 1.282 inches |
| Head Style: | |
| Flat countersunk | |
| Head Diameter: | |
| Between 0.447 inch | es and 0.507 inches |
| Grip Diameter: | |
| Between 0.2485 incl | hes and 0.2495 inches |
| Internal Drive Style | |
| Offset cruciform (tor | que set) |
| Thread Diameter: | |
| 0.250 inches | |
| Grip Length: | |
| Between 0.759 inch | es and 0.779 inches |
| Features Provided: | |
| Dry film lubricant | |
| Thready Qty Per In | ch (tpi): |
| 28 | |
| Countersink Angle | : |
| Between 99.0 degre | es and 101.0 degrees |
| Material: | |
| Stainless steel | |
| Material Specificati | on: |
| Ams5844 assn stan | dard single material response |
| Surface Treatment: | |
| Passivate | |
| Surface Treatment | Specification: |
| Qq-p-35 federal spe | cification single treatment response and mil-I-46010, tyi military specification single treatment respons |
| Thread Series Desi | gnator: |
| Unjf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

NSN 5305-01-398-6336

Close Tolerance Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-I-46010 spec.