NSN 5305-01-398-6336

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-398-6336 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.498 inches **Fastener Length:** Between 1.252 inches and 1.282 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.447 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.759 inches and 0.779 inches **Features Provided:** Dry film lubricant Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Stainless steel **Material Specification:** Ams5844 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response and mil-l-46010, tyi military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-398-6336

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-I-46010 spec.