

View Online at <https://aerobasegroup.com/nsn/5305-01-398-6338>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.914 inches

Fastener Length:

Between 3.211 inches and 3.241 inches

Head Style:

Spline drive shear head

Head Height:

Between 0.390 inches and 0.410 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.146 inches first hole

Head Minor Diameter:

1.096 inches

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.750 inches

Grip Length:

Between 2.297 inches and 2.327 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.072 inches first hole and 3.113 inches first hole

Surface Finish:

32.0 microinches

Material:

Nickel alloy 718

Material Specification:

Ams 5662 federal specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0