

View Online at <https://aerobasegroup.com/nsn/5305-01-398-7058>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.600 inches and 0.625 inches

**Fastener Length:**

Between 0.970 inches and 1.000 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.218 inches and 0.226 inches

**Head Height:**

Between 0.134 inches and 0.138 inches

**First Diameter From Head:**

Between 0.102 inches and 0.107 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.370 inches and 0.375 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.138 inches

**Width Across Flats:**

Between 0.1094 inches and 0.1111 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response and ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unrc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0