NSN 5305-01-398-7058

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-398-7058 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.600 inches and 0.625 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **First Diameter From Head:** Between 0.102 inches and 0.107 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.370 inches and 0.375 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response and ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrc

N/a

Shelf Life:

NSN 5305-01-398-7058

Externally Relieved Body Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0