

View Online at <https://aerobasegroup.com/nsn/5305-01-398-8617>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.813 inches and 0.875 inches

**Fastener Length:**

0.875 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.159 inches and 0.164 inches

**Head Height:**

Between 0.159 inches and 0.164 inches

**Locking Feature:**

Pellet threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.164 inches

**Width Across Flats:**

Between 0.140 inches and 0.142 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

155000 pounds per square inch

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel fastener

**Material Specification:**

Fed66 federal standard all material responses fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response fastener

**Thread Series Designator:**

Unrc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0