Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-400-0507

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.360 inches and 0.390 inches |
| Fastener Length: |
| Between 0.985 inches and 1.015 inches |
| Head Style: |
| Knurled no. 4 |
| Head Diameter: |
| Between 0.438 inches and 0.443 inches |
| Head Height: |
| Between 0.235 inches and 0.265 inches |
| First Diameter From Head: |
| 0.115 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.625 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |
| |