NSN 5305-01-400-2847



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-400-2847 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.514 inches **Fastener Length:** 0.514 inches **Head Style:** Drive **Head Diameter:** Between 0.495 inches and 0.505 inches **Head Height:** 0.179 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Material Specification:** Fed-std66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Special Features:** Head with molded washer, nylon per mil-m-20693; epoxy coated head **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A500d0

NSN 5305-01-400-2847

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5002 spec.