

View Online at <https://aerobasegroup.com/nsn/5305-01-400-3695>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.240 inches and 0.260 inches

**Fastener Length:**

1.000 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.357 inches and 0.404 inches

**Head Height:**

Between 0.099 inches and 0.110 inches

**First Diameter From Head:**

Between 0.125 inches and 0.135 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.750 inches

**Point Style:**

Flat

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304

**Material Specification:**

Astm a581 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.